

Material Safety Data Sheet
 May be used to comply with
 OSHA's Hazard Communication Standard,
 29 CFR 1910.1200. Standard must be
 consulted for specific requirements.

U.S. Department of Labor
Occupational Safety and Health Administration
 (Non-Mandatory Form)
 Form Approved
 OMB No. 1218-0072



IDENTITY (As Used on Label and List)

TENSIVE® CONDUCTIVE ADHESIVE GEL

Note: Blank spaces are not permitted. If any item is not applicable, or no information is available, the space must be marked to indicate that.

Section I

Manufacturer's Name

PARKER LABORATORIES, INC.

Address (Number, Street, City, State and ZIP Code)

286 ELDRIDGE ROAD

FAIRFIELD, NJ 07004

Emergency Telephone Number

Telephone Number for Information

(973) 276-9500

Date Prepared

SEPTEMBER 2009

Signature of Preparer (optional)

Section II – Hazardous Ingredients/Identity Information

Hazardous Components (Specific Chemical Identity; Common Name(s))	OSHA PEL	ACGIH TLV	Other Limits Recommended	% (optional)
NONE				

Section III – Physical/Chemical Characteristics

Boiling Point	N/A	Specific Gravity (H²O = 1)	1.0
Vapor Pressure (mm Hg.)	N/A	Melting Point	N/A
Vapor Density (AIR = 1)	N/A	Evaporation Rate (Butyl Acetate = 1)	N/A
Solubility in Water	SOLUBLE		

Appearance and Odor

VISCOUS, AMBER COLORED GEL; PERFUMED ODOR

Section IV – Fire and Explosion Hazard Data

Flash Point (Method Used) N/A	Flammable Limits N/A	LEL N/A	UEL N/A
Extinguishing Media USE EXTINGUISHING MEDIA APPROPRIATE FOR SURROUNDING FIRE.			
Special Fire Fighting Procedures NONE			

Unusual Fire and Explosion Hazards

NONE

